

## DECLARATION OF PERFORMANCE

Orchard NSBP Mixed Calibrated Project Pack

**1. Product Type:** Quartzitic Sandstone

**2 Unique Identification Code(s):** NPPORNSBPMx-PP

**3. Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

Commercial And Domestic Paving For External Use

**4. Manufacturer:** Natural Paving Products (UK) Ltd (Stone Exporters (India) Pvt Ltd.)  
Vidisha  
India

**5. Authorised Representative:** Steve Milburn

**6. System of System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V of the CPR:** Level 4

**7. Harmonised Standard:** EN1341:2012

**8. Notified Body:** N/A

**9. Declared Performance**

Essential Characteristic	Performance	Harmonised Technical Specification EN1341:2012
Release Of Dangerous Substances	NPD	4.11
Compressive Strength - Lowest Expected Value	120.38MPa	EN1926 4.4
Slip Resistance Wet Value	56	EN14231 4.6.1
Slip Resistance Dry Value	62	EN14231 4.6.1
Skid Resistance	NPD	4.6.2
Freeze/Thaw Resistance – Mean values before and after freeze/thaw test	165/140.7MPa	EN12371 4.3.1
Freeze/Thaw Resistance – De-icing salts	NPD	4.3.2
Polishing In Use	NPD	4.6.3
Water Absorption	2.6%	EN13755
Abrasion Resistance	14.5mm	EN14157

**10.** The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Signed for and on behalf of the manufacturer by:**

**Name and function:** Mark Wall, Managing Director

**Place and date of issue:**

Belton Road  
Sandtoft  
Doncaster  
North Lincolnshire  
DN8 5SX

**Signature:**

A handwritten signature in black ink, appearing to read 'M. Wall', written over a light grey horizontal line.

27<sup>th</sup> April 2016